


Dorngefertigter Haspelschlauch für Wasser und flüßige Löschmittel, geeignet für Feuerwehrtankwagen. Starke und flexible Ausführung. Gemäß **BS3169/1986 A2**


Mandrel built hose for water and liquid fire extinguishing mediums. Suitable for reels on trucks for fire brigades. Strong and flexible structure. Complies with **BS3169/1986 A2**



### Technische Daten

<b>Seele</b>	Schwarzes EPDM Gummi, glatt, beständig gegen Wasser und Feuerlöschschaum.
<b>Einlagen</b>	Synthetische Textileinlagen.
<b>Decke</b>	Schwarzes EPDM Gummi, abrieb- und witterungsbeständig. Stoffgemustert.
<b>Betriebsdruck</b>	55 bar
<b>Soll-Platzdruck</b>	180 bar
<b>Temperatur</b>	-30° C + 80°C
<b>Markierung</b>	 THOR BS3169/1986 A2- size mm / 55 Bar (geprägt)

### Technical Characteristics

<b>Tube</b>	Black smooth SBR/NR rubber, resistant to water and extinguishing foam.
<b>Reinforcement</b>	High tensile textile plies.
<b>Cover</b>	Black SBR/NR rubber, resistant to abrasion and weather conditions. Fabric impression.
<b>Working Pressure</b>	55 bar
<b>Nominal Burst Pressure</b>	180 bar
<b>Temperature</b>	-30°C +80°C
<b>Marking</b>	 THOR BS3169/1986 A2- size mm / 55 Bar (embossed)

### Abmessungen / Sizes

Innendurchmesser Inner Diameter	Wanddicke Wall Thickness	Außendurchmesser Outside Diameter	Gewicht Weight	Biegeradius Bendino Radius
mm	mm	mm	Kg/m	mm
19	6,5	32	0,59	100
25	6	37	0,73	100