

T6711



SCAMO/SP CAJ

Dorngefertigter Abgasschlauch, geeignet auch für Wärmeaustauschanlagen auf Privatbooten. Gemäß **SAE J 2006:03 R2 – ISO 13363:04 Type 2 Class B**. Freigabe **LLOYD'S REGISTER nr. 96/00127- RINA nr. DIP072110MI**



Marine exhaust hose suitable also for cooling the heat exchangers on pleasure boats. Manufactured in accordance with **SAE J 2006:03 R2 – ISO 13363:04 Type 2 Class B**. Fully type approved by **LLOYD'S REGISTER nr.96/00127- RINA nr. DIP07211MI**



Technische Daten

Seele	Schwarzes glattes Gummi beständig gegen Abgas und Meereswasser.
Einlagen	Synthetische Textileinlagen und Stahldrahtspirale.
Decke	Schwarzes Gummi, beständig gegen Abrieb, Hitze und Meeresluft. Glatte Decke. Stoffgemustert.
Betriebsdruck	3 bar
Temperatur	- 30°C + 100°C
Markierung	 ITALY SCAMO/SP ® MARINE WET EXHAUST LLOYD'S REGISTER nr.96/00127 RINA nr.DIP017211MI (in grüner Farbe) +  SAE J 2006:03 R2 – ISO 13363 : 04 Type 2 CLASS B (Ø+quarter/year) (geprägt)

Technical Characteristics

Tube	Black smooth exhausts and sea water resistant rubber
Reinforcement	High tensile textile plies and embedded steel wire helix.
Cover	Black rubber resistant to abrasion, heat and marine environment. Corrugated with fabric impression
Working Pressure	3 bar
Temperature	- 30°C + 100°C
Marking	 ITALY SCAMO/SP ® MARINE WET EXHAUST LLOYD'S REGISTER nr.96/00127 RINA nr. DIP017211MI (in green colour) +  SAE J2006:03 R2 – ISO 13363 : 04 Type 2 CLASS B (Ø + quarter/year) (embossed)

Abmessungen / Sizes

Innendurchmesser Inner Diameter	Gewicht Weight	Biegeradius Bending Radius
mm	Kg/m	mm
25	0.75	65
38	0.87	80
40	0.90	80
45	1.00	90
50	1.10	100
53	1.28	105
57	1.38	115
60	1.45	120
63	1.69	125
75	1.98	150

Innendurchmesser Inner Diameter	Gewicht Weight	Biegeradius Bending Radius
mm	Kg/m	mm
80	2.08	160
90	2.54	180
100	2.81	200
110	3.00	220
114	3.32	225
120	3.52	235
125	3.60	250
130	3.70	260
142	4.00	280
150	4.80	300