

T877

SFUCEM 40N


Telephone: 01708 686600

Dorngefertigter Zementsiloschlauch geeignet zum Durchleiten von Zement, Kalk, Kies und pulverförmigen abrasiven Medien mit kleiner Teilchengröße. Geeignet auch für Tanklastwagen


Mandrel built bulk material delivery hose suitable for abrasive materials such as cement, chalk, lime and abrasive powders with small granules. Suitable for silo discharging and on tank trucks.



Technische Daten

Seele	Schwarzes, glattes Gummi, abriebfest
Einlagen	Synthetische Textileinlagen.
Decke	Schwarzes, glattes Gummi, abrieb- und witterungsbeständig. Stoffgemustert.
Betriebsdruck	6 bar
Soll-Platzdruck	18 bar
Temperatur	-40 °C +70 °C
Markierung	 BULK MATERIAL DELIVERY W.P. 6 BAR – 85 PSI (in orangener Schrift)

Technical Characteristics

Tube	Black smooth rubber, resistant to abrasion.
Reinforcement	High tensile textile plies.
Cover	Black, smooth, weather and abrasion resistant rubber. Fabric impression.
Working Pressure	6 bar
Nominal Burst Pressure	18 bar
Temperature	-40 °C +70 °C
Marking	 BULK MATERIAL DELIVERY W.P 6 BAR 85 PSI (in orange letters)

Abmessungen / Sizes

Innendurchmesser Inner Diameter	Wanddicke Wall Thickness	Außendurchmesser Outside Diameter	Seele Tube	Gewicht Weight
mm	mm	mm	mm	Kg/m
102	5	112	2,5	1,93